

SECTION V HEALTH HAZARD DATA	
THRESHOLD LIMIT VALUE	10 ppm (based on acetic acid)
EFFECTS OF OVEREXPOSURE	Irritates eyes. Prolonged or repeated contact may irritate skin.
EMERGENCY AND FIRST AID PROCEDURES	Flush with water.

SECTION VI REACTIVITY DATA			
STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	Air or moisture causes polymerization
INCOMPATIBILITY (Materials to avoid)		None known	
HAZARDOUS DECOMPOSITION PRODUCTS SiO <sub>2</sub> , CO <sub>2</sub> & traces of incompletely burned carbon products.			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII SPILL OR LEAK PROCEDURES	
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Use absorbent material providing proper protective equipment.	
WASTE DISPOSAL METHOD Can be land filled or burned in accordance with local regulations.	

SECTION VIII SPECIAL PROTECTION INFORMATION		
RESPIRATORY PROTECTION (Specify type) Acid type (if necessary)		
VENTILATION	LOCAL EXHAUST	SPECIAL
	MECHANICAL (General) X	OTHER
PROTECTIVE GLOVES	Rubber or Plastic	EYE PROTECTION Safety glasses
OTHER PROTECTIVE EQUIPMENT As required by your company.		

SECTION IX SPECIAL PRECAUTIONS	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Store below 90° F. Use reasonable care.	
OTHER PRECAUTIONS	

PREPARED BY

CPO-205-3 Rev.

BOE-C6-0227492